

# Submersible Pump PW100A Series

To be use with clean water, non-aggressive water and slightly dirty (grey) wastewater.

- To drain the ground water.
- To be application to the sprinkler for vegetations of parks.
- · To be used to circulate water in garden ponds.
- · To be application to the fishing.



### **Specifications**

Model	PW100A	PW100AF
Power (W)	125	125
Cycle (Hz)	50	50
Voltage (V)	220	220
Amp (A)	1.0	1.0
Max Head (M)	6.5	6.5
Max Flow rate (LPM)	80	80
Max suction (M)	5	5
Outlet (in.)	1	1
Cable (M)	6	6
Float switch	No	Yes
N.W. (kg)	4.1	4.3
G.W. (kg)	4.7	4.9
Packaging size (mm)	150*140*241	155*140*24

#### **Feature**



The joint size1"
Can be removed
PIPE SIZE 1"



1/2 PIPE SIZE 1/2"
3/4 PIPE SIZE 3/4"
Have clip lock the rubber hose.



Have Strainer prevents debris from clogging the pump



Power plug
Length 6 meters
Groundwire for
more safety



Genuine Copper coil with Thermal Overload Protection



Pump casing
High polymer
plastic
Strong and durable

#### **Dimension**



## Performance curves

